



# Briquette Storage

F37 Series & Heat Sealers

SELF-CONTAINED STORAGE SOLUTIONS ■ ADJUSTABLE LOADING HEIGHTS ■ LOW POWER CONSUMPTION

**FERCELL**

[www.fercell.com](http://www.fercell.com)

# Rotating Carousel Bagging Station - F37 Series

The F37-Series of automatic carousel bagging stations, are completely self-contained, available with 6, 8, 12 or 24 loading stations. The loading station height is fully adjustable in height, with each station accommodating a 300mm diameter plastic sack, with deflector clamps.

The carousel is driven by a high-torque geared reduction drive via a circular rack and pinion assembly, to ensure minimal energy consumption and reliable service.

The F37-Series is equipped with a TC130 microprocessor control. With a backlit LED touch screen providing clear input information, easy access and adjustment to the programmes, for automatically counting of briquettes from the associated briquette press. The default program auto-indexes to the consecutive station once the pre-programmed number of briquettes has been reached in the preceding station.



Image: F37 Series Rotating Bagging Carousel



## TECHNICAL SPECIFICATION

MODEL	Stations	Station ø	Station Height mm	Carousel ø mm	Maximum Loading Kgs	Drive	Control	Weight Kgs	Finish
F3720	6	300 mm	400 - 1,000	1,000	180	Direct 0.18kW 415v 50Hz 3Phs	TC130	128	RAL7032/7035 + zinc plated
F3730	8	300 mm	400 - 1,000	1,200	200	Direct 0.18kW 415v 50Hz 3Phs	TC130	145	RAL7032/7035 + zinc plated
F3740	12	300 mm	400 - 1,000	1,800	300	Direct 0.25kW 415v 50Hz 3Phs	TC130	162	RAL7032/7035 + zinc plated
F3750	24	300 mm	400 - 1,000	2,000	300	Direct 0.25kW 415v 50Hz 3Phs	TC130	162	RAL7032/7035 + zinc plated

# HM-6500 Heat sealing m/c with HM-65 Stand Kit

The HM-6500 is a large capacity energy saving heavy duty foot operated impulse heat sealer, with an electronic timer for complete control of heating and cooling cycles.

With a cable operated foot pedal, you have flexibility for the installation for the heat sealer.

The HM-6500 provides a great addition to the bagging carousel. Once bags are full and removed from the carousel, they can be sealed for airtight neat storage.

## TECHNICAL SPECIFICATION

MODEL	HM-6500
Maximum sealing length	680 mm
Maximum film thickness	2 x 1000 gauge (2 x 250 micron)
Voltage	240V 50Hz- 110V conversion
Power consumption	360 watts per seal




Image: HM-6500 Heat Sealer with Stand

The F37 Series rotating bagging carousel and HM-6500 make the perfect pair.

## FEATURED BENEFITS

- Neat solution to easily provide sealed contents ready for sale
- Compact storage
- Low energy consumption



Fercell provide complete industrial recycling and size reduction systems and industrial ventilation equipment to control pollutants.

Our range of machinery includes industrial shredders, briquette presses, granulators, drainage presses, conveyors and ancillaries, helping you to efficiently and responsibly recycle, often for revenue.

Our ventilation systems will ensure your factory legally and safely extracts all types of dust, exhaust or welding fumes and paint spray or powder.

## CONTACT US

Fercell Engineering Limited  
Old Mill Lane, Aylesford, Kent  
ME20 7DT, UK

t: 01622 791414

e: [info@fercell.com](mailto:info@fercell.com)

INDUSTRIAL RECYCLING AND SIZE REDUCTION SYSTEMS AND VENTILATION SYSTEMS

**FERCELL**

[www.fercell.com](http://www.fercell.com)